



NO LEAD "ALL WEATHER" PIPE WRAP TAPE

APPLICATIONS:

Boshart's "All Weather" Pipe Wrap Tape gives a uniform protective coating against abrasion and corrosive action for steel pipe, fittings and electrical conduit systems. It provides a physical barrier that is moisture proof, inert and non-conducting. Whether you are protecting metal piping/mill coated pipe systems above or below ground, overhead piping/electrical conduit and fittings in industrial applications, this tough PVC plastic tape with high tack adhesive resists corrosive action by salt water, soil acids, alkalis and salts.

SPECIFICATIONS & INDUSTRY LISTINGS:

- Can be used on all types of pipe and fittings, including steel, galvanized, electrical conduit, cast and ductile iron.
- Black Pipe Wrap tape is listed by the International Association of Plumbing & Mechanical Officials (IAPMO) and carries the shield. Only Boshart's PW2-10NL black pipe wrap tape is tested to ASTM D-1000 standard.
- Provides excellent insulating capacities and superior abrasion resistance
- Resists/reduces corrosion problems caused by salts, salt water, soil acids and alkalis.
- Provides a dielectric barrier, prevents dielectric corrosion between buried steel pipe and soil minerals.
- Resists common chemicals and chemical vapors and protects against fungus and bacteria in many applications.
- Highly conformable remains pliable in a wide range of temperature and working environments, resists the effects of outdoor weathering and sunlight exposure.

PHYSICAL PROPERTIES:

Width: 2.0"

Thickness: 10 mils (0.25mm)

Length: 100 ft.

Tensile Strength: 19.84 lbs./in., 9 kgf/25mm (3.528 N/mm)

Elongation At Break: 200 %

Adhesion to Steel: 19.75 oz./in., 0.56 kgf/25mm (0.219 N/mm)

Operating Temperature: 15°F to 176°F (-10°C to 80°C)



UPC Listed



PART NO.

DESCRIPTION

PW2-10NL

BLACK - Width 2" x 100 ft. x Thickness 10 MIL (0.25mm)

PW2-G10NL

GREEN - Width 2" x 100 ft. x Thickness 10 MIL (0.25mm)



25 Whaley Ave., Milverton, Ontario, Canada N0K 1M0

Tel: (519)-595-4444

Toll Free: (800)-561-3164

Fax: (519)-595-4380

Web: www.boshart.com