

**Oatey**

the choice of plumbing professionals

**QUIET  
PIPES®**




**SILENCE THE WATER HAMMER**  
Quiet Pipes® Water Hammer Arrestors

# WHAT IS WATER HAMMER?

The persistent clanking, banging and pounding in your pipes behind the wall might sound like a tiny war is being waged but have no fear, Oatey Quiet Pipes® is finally here.

That annoying sound is called water hammer and it can happen just about anywhere in any type of building. Water hammer can occur when flushing your toilet, turning on or off a water valve or even with the changing of cycles in your washing machine. The change in water flow causes waves inside the pipes that create a hammer sound. Depending on the size of the plumbing system, water hammer can cause serious damage to pipes.


Left untreated, water hammer can harm different parts of the plumbing system including pipe supports, faucets, valves and even water heaters.



# THERE'S ONLY ONE SOLUTION.

Try Oatey Quiet Pipes® Hammer Arrestors to help solve current and potential water hammer problems.




Quiet Pipes use a piston design to help absorb the water shock in the system. When a valve is closed abruptly, the water moves into the pressurized chamber of the hammer and the water pressure is absorbed to prevent banging within the pipeline. Once the water flow comes out of the chamber, it is dissipated to the rest of the water line.



# FINDING THE RIGHT PRODUCT FOR THE JOB.

## COMMERCIAL

### Multi-Fixture Plumbing Groups



#### Sizing/Placement Guideline

The proper arrestor size depends on the total number of fixture units on each hot and cold branch line. Each arrestor will be placed at the end of the branch line.


#### Quiet Pipes Arrestors

ANSI/ASSE 1010-2004  
Certified A–F size arrestors.



## RESIDENTIAL

### Single-Fixture and Private Plumbing Groups



#### Sizing/Placement Guideline

For use on dishwashers, washing machines and tub/shower valves.



#### Quiet Pipes Arrestors

ANSI/ASSE 1010-2004  
Certified AA size arrestors.






# WHY CHOOSE OATEY QUIET PIPES HAMMER ARRESTORS?

## FEATURES & BENEFITS

- Quiet Pipes® utilizes a polypropylene **piston design** with two NBR O-rings to absorb the shock in the system.
- Oatey Quiet Pipes® water hammer arrestors carry a **limited warranty** that is equal in duration to the lifetime of the plumbing system in which they are installed. All other terms and conditions of the Limited Warranty shall apply to these products. See [Oatey.com/warranty](https://www.oatey.com/warranty) for warranty details.
- Quiet Pipes come in a **range of connection types** including MIP, CPVC, PEX and more.
- Quiet Pipes conform to **ANSI/ASSE 1010–2004** and are listed and approved for installation with no access panel required.
- Through **12 manufacturing and distribution facilities**, Oatey designs, manufactures and sources over 10,000 plumbing related products. Nearly 80% of our products are manufactured in the United States, and distributed in more than 70 countries worldwide.



# RESIDENTIAL & COMMERCIAL CODE REQUIREMENTS



## ASSE 1010

All Oatey Quiet Pipes are ASSE 1010 Certified. UPC, IPC, and NPCC all require the installation of ASSE 1010 Certified Water Hammer Arrestors on all quick-closing valves to control water hammer in both residential and commercial applications.



## UPC

### 609.10 Water Hammer.

Building water supply systems where quick-acting valves are installed shall be provided with water hammer arrestor(s) to absorb high pressures resulting from the quick closing of these valves. Water hammer arrestors shall be approved mechanical devices in accordance with ASSE 1010 or PDI-WH 201 and shall be installed as close as possible to quick-acting valves.

## IPC

## IPC

### 604.9 Water hammer.

The flow velocity of the water distribution system shall be controlled to reduce the possibility of water hammer. A water hammer arrestor shall be installed where quick-closing valves are utilized. Water hammer arrestors shall be installed in accordance with the manufacturer's instructions. Water hammer arrestors shall conform to ASSE 1010.



## NPCC

### A-2.6.1.9.(1) Water Hammer Prevention.

Water hammer is a buildup of pressure in a length of horizontal or vertical pipe that occurs when a valve or faucet is closed suddenly. The longer the pipe and the greater the water velocity, the greater the pressure exerted on the pipe, which can be many times the normal static water pressure and be sufficient to damage the piping system. Since air chambers made from a piece of vertical pipe do not provide acceptable protection, pre-manufactured water hammer arrestors are required to address this potential problem. Water hammer arrestors need not be installed at every valve or faucet, nor in every piping system.

# SPEC'D FOR THE PROS.

Oatey Quiet Pipes will go head-to-head with any water hammer arrestor manufacturer, and outperform the competition in nearly every major category. See for yourself why Quiet Pipes are the choice of plumbing professionals everywhere.

**TRUSTED**

- Comprehensive technical support
- Reputable leadership in the plumbing industry
- Experienced customer service professionals

**STRONG**

- Regional distribution: Cleveland, Dallas, Denver, Newark, Toronto and Monterrey, Mexico
- Multiple manufacturing locations: Colorado, Minnesota, Nebraska, Ohio and China
- ISO 9001 Certified
- Twenty-three categories with a broad range of products

**EFFICIENT**

- VMI - Vendor Managed Inventory
- EDI - Paperless ordering, invoices and ship notices
- Automatic acknowledgments and confirmations of shipments
- Economical minimum orders for prepaid freight
- Multi-branded promotional opportunities

**SAFE**

- C-TPAT participant



## OATEY® GOES HEAD-TO-HEAD

YES ☒ NO ☐

|                          | Oatey®                              | Competitor A                        | Competitor B                        | Competitor C                        | Competitor D                        |
|--------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Permanent Gas Charge     | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Dual O-ring or Better    | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| ASSE 1010 Certified AA-F | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| O Chamber Seams          | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/>            | <input type="checkbox"/>            | <input type="checkbox"/>            |



# QUIET PIPES®

## RESIDENTIAL PRODUCT LINE

### STRAIGHT & WASHING MACHINE



| ITEM NO. | DESCRIPTION   | CASE PACK | UPC          |
|----------|---|-----------|--------------|
| 34457    | Quiet Pipes Hammer Arrestor, 1/2" Male Sweat, Straight, AA  | 30        | 038753344577 |
| 34458    | Quiet Pipes Hammer Arrestor, 1/2" CPVC Female, Straight, AA | 30        | 038753344584 |
| 34459    | Quiet Pipes Hammer Arrestor, 1/2" CPVC Male, Straight, AA   | 30        | 038753344591 |
| 34460    | Quiet Pipes Hammer Arrestor, 1/2" F1960, Straight, AA       | 30        | 038753344607 |
| 34461    | Quiet Pipes Hammer Arrestor, 1/2" F1960, Straight, AA       | 30        | 038753344614 |
| 34463    | Quiet Pipes Hammer Arrestor, 3/4" Male Sweat, Straight, AA  | 30        | 038753344638 |
| 39177    | Quiet Pipes Hammer Arrestor, 1/2" MIP, Straight, AA         | 6         | 038753391779 |
| 38600    | Quiet Pipes Washing Machine Supply Line Shock Absorber, AA  | 6         | 038753386003 |

### PEX TEE



| ITEM NO. | DESCRIPTION   | CASE PACK | UPC          |
|----------|---|-----------|--------------|
| 34471    | Quiet Pipes Hammer Arrestor, 1/2" PEX F1960 Tee, AA | 30        | 038753344713 |
| 34472    | Quiet Pipes Hammer Arrestor, 1/2" PEX F1807 Tee, AA | 30        | 038753344720 |

### COMPRESSION TEE



| ITEM NO. | DESCRIPTION  | CASE PACK | UPC          |
|----------|--|-----------|--------------|
| 34473    | Quiet Pipes Hammer Arrestor, 1/4" O.D. Compression Tee, AA | 30        | 038753344737 |
| 34474    | Quiet Pipes Hammer Arrestor, 3/8" O.D. Compression Tee, AA | 30        | 038753344744 |

### FEMALE COMPRESSION TEE



| ITEM NO. | DESCRIPTION   | CASE PACK | UPC          |
|----------|---|-----------|--------------|
| 34475    | Quiet Pipes Hammer Arrestor, 1/4" O.D. Compression x Female Tee, AA | 30        | 038753344751 |
| 34465    | Quiet Pipes Hammer Arrestor, 3/8" O.D. Compression x Female Tee, AA | 30        | 038753344652 |
| 34467    | Quiet Pipes Hammer Arrestor, 5/8" O.D. Compression x Female Tee, AA | 30        | 038753344676 |

#### TO PLACE AN ORDER

Contact your local Oatey Representative  
800-321-9532 | Oatey.com



# QUIET PIPES®

## COMMERCIAL PRODUCT LINE

### STRAIGHT MALE IRON PIPE



| ITEM NO. | DESCRIPTION  | CASE PACK | UPC          |
|----------|--|-----------|--------------|
| 34481    | Quiet Pipes Hammer Arrestor, 1/2" MIP, Straight, A | 12        | 038753344812 |
| 34484    | Quiet Pipes Hammer Arrestor, 3/4" MIP, Straight, B | 30        | 038753344843 |
| 34485    | Quiet Pipes Hammer Arrestor, 1" MIP, Straight, C   | 24        | 038753344850 |
| 34479    | Quiet Pipes Hammer Arrestor, 1" MIP, Straight, E   | 6         | 038753344799 |
| 34480    | Quiet Pipes Hammer Arrestor, 1" MIP, Straight, F   | 6         | 038753344805 |

### STRAIGHT MALE SWEAT/PRESS FITTING



| ITEM NO. | DESCRIPTION   | CASE PACK | UPC          |
|----------|---|-----------|--------------|
| 34486    | Quiet Pipes Hammer Arrestor, 1/2" Male Sweat/Press, Straight, A | 30        | 038753344867 |
| 34483    | Quiet Pipes Hammer Arrestor, 3/4" Male Sweat/Press, Straight, B | 30        | 038753344836 |
| 34487    | Quiet Pipes Hammer Arrestor, 1" Male Sweat/Press, Straight, C   | 24        | 038753344874 |
| 34488    | Quiet Pipes Hammer Arrestor, 1" Male Sweat/Press, Straight, D   | 6         | 038753344881 |
| 34489    | Quiet Pipes Hammer Arrestor, 1" Male Sweat/Press, Straight, E   | 6         | 038753344898 |
| 34490    | Quiet Pipes Hammer Arrestor, 1" Male Sweat/Press, Straight, F   | 6         | 038753344904 |

### CPVC SOCKET ASTM D 2846



| ITEM NO. | DESCRIPTION  | CASE PACK | UPC          |
|----------|--|-----------|--------------|
| 34491    | Quiet Pipes Hammer Arrestor, 1/2" CPVC Socket, Straight, A | 24        | 038753344911 |
| 34492    | Quiet Pipes Hammer Arrestor, 3/4" CPVC Socket, Straight, B | 24        | 038753344928 |
| 34477    | Quiet Pipes Hammer Arrestor, 1" CPVC Socket, Straight, C   | 12        | 038753344775 |

### ASTM PEX F1807 CRIMP & ASTM PEX F1960 GRIP



| ITEM NO. | DESCRIPTION  | CASE PACK | UPC          |
|----------|--|-----------|--------------|
| 34482    | Quiet Pipes Hammer Arrestor, 1/2" F1807, Straight, A | 12        | 038753344829 |
| 34493    | Quiet Pipes Hammer Arrestor, 3/4" F1807, Straight, B | 30        | 038753344935 |
| 34494    | Quiet Pipes Hammer Arrestor, 1" F1807, Straight, C   | 24        | 038753344942 |
| 34476    | Quiet Pipes Hammer Arrestor, 1/2" F1960, Straight, A | 12        | 038753344768 |
| 34495    | Quiet Pipes Hammer Arrestor, 3/4" F1960, Straight, B | 30        | 038753344959 |
| 34496    | Quiet Pipes Hammer Arrestor, 1" F1960, Straight, C   | 24        | 038753344966 |



# OATEY QUIET PIPES® HAMMER ARRESTORS SIZE AA

## SPECIFICATIONS

Oatey Quiet Pipes Hammer Arrestors shall be installed in any small diameter pipe supply application which could experience water hammer due to quick closing valves or faucets. Arrestor chambers shall be specifically sized to accommodate and dissipate energy generated by such valves and faucets. Arrestors shall be effective when installed at any angle. Arrestor shall be made of lead-free copper and include a polypropylene piston with two NBR O-rings. Arrestors shall be ANSI/ASSE1010-2004 certified and approved for installation with no access panel required. Compatible with press fittings or push fittings.

## FEATURES & MATERIALS

|                    |  |
|--------------------|--|
| Arrestor Body      | Copper (Type L)  |
| Piston             | Polypropylene with two NBR O-rings   |
| Piston Lubrication | Dow Corning Molykote 111   |
| Fittings Available | Male Sweat, Female CPVC, Male CPVC, F1807 PEX & F1960 PEX (no lead brass C46400) |

## PERFORMANCE SPECIFICATIONS

|                      |              |
|----------------------|--------------|
| Temperature Range    | 33° – 180° F |
| Max Working Pressure | 0 – 60 PSI   |

## LISTINGS & CODE APPROVALS

|                     |
|---------------------|
| ANSI/ASSE 1010–2004 |
| cUPC                |




## DIMENSIONS


|                             |            |             |           |           |           |       |        |            |
|-----------------------------|------------|-------------|-----------|-----------|-----------|-------|--------|------------|
| Arrestor Size               | AA         | AA          | AA        | AA        | AA        | AA    | AA     | AA         |
| Product #                   | 34457      | 34458       | 34459     | 34460     | 34461     | 39177 | 38600  | 34463      |
| Arrestor Body Diameter [A]: | 0.875"     | 0.875"      | 0.875"    | 0.875"    | 0.875"    | 0.87" | 0.87"  | 0.875"     |
| Overall Height [B]:         | 4.84"      | 2.95"       | 3.63"     | 3.83"     | 3.85"     | 2.75" | 4.38"  | 5.36"      |
| Fitting Type [C]:           | Male Sweat | Female CPVC | Male CPVC | F1960 PEX | F1807 PEX | MIP   | Branch | Male Sweat |
| Fitting Size [C]:           | 1/2"       | 1/2"        | 1/2"      | 1/2"      | 1/2"      | 1/2"  | 3/4"   | 3/4"       |

## PRODUCT SELECTOR


| ✓ | Product Number | Description          | ✓ | Product Number | Description                     |
|---|----------------|----------------------|---|----------------|---------------------------------|
|   | 34457          | AA, 1/2" Male Sweat  |   | 34461          | AA, 1/2" F1807 PEX              |
|   | 34458          | AA, 1/2" Female CPVC |   | 39177          | AA, 1/2" MIP                    |
|   | 34459          | AA, 1/2" Male CPVC   |   | 38600          | AA, 3/4" x 3/4" Washing Machine |
|   | 34460          | AA, 1/2" F1960 PEX   |   | 34463          | AA, 3/4" Male Sweat             |




F1960 PEX



F1807 PEX



MALE SWEAT




FEMALE CPVC

\*Limited Lifetime Warranty – See [Oatey.com/warranty](http://Oatey.com/warranty) for details.



**“MY CUSTOMER SAID QUIET PIPES WORK  
LIKE MAGIC. THAT’S GOOD ENOUGH FOR ME.”**



**QUIET  
PIPES®**



# OATEY QUIET PIPES® HAMMER ARRESTORS TEE FITTING

## SPECIFICATIONS

Oatey Quiet Pipes Hammer Arrestors shall be installed in any diameter pipe supply application which could experience water hammer due to quick closing valves or faucets. Arrestor chambers shall be specifically sized to accommodate and dissipate energy generated by such valves and faucets. Arrestors shall be effective when installed at any angle. Arrestor shall be made of lead-free copper and include a polypropylene piston with two NBR O-rings. Arrestors shall conform to ANSI/ASSE1010-2004, listed and approved for installation with no access panel required.

## FEATURES & MATERIALS

|                    |  |
|--------------------|--|
| Arrestor Body      | Copper (Type L)  |
| Piston             | Polypropylene with two NBR O-rings   |
| Piston Lubrication | Dow Corning Molykote 111   |
| Fittings Available | Female Compression, O.D. Compression, F1807 PEX & F1960 PEX (no lead brass C46400) |

## PERFORMANCE SPECIFICATIONS

|                      |              |
|----------------------|--------------|
| Temperature Range    | 33° – 180° F |
| Max Working Pressure | 0 – 60 PSI   |

## LISTINGS & CODE APPROVALS

|                     |
|---------------------|
| ANSI/ASSE 1010–2004 |
| cUPC                |




## DIMENSIONS

|                             |            |              |              |            |           |           |              |
|-----------------------------|------------|--------------|--------------|------------|-----------|-----------|--------------|
| Arrestor Size               | AA         | AA           | AA           | AA         | AA        | AA        | AA           |
| Product #                   | 34473      | 34475        | 34465        | 34474      | 34471     | 34472     | 34467        |
| Arrestor Body Diameter [A]: | 0.875"     | 0.875"       | 0.875"       | 0.875"     | 0.875"    | 0.875"    | 0.875"       |
| Overall Height [B]:         | 2.75"      | 2.75"        | 2.75"        | 2.75"      | 2.75"     | 2.75"     | 2.75"        |
| Connection Type [C]:        | O.D. Comp. | Female Comp. | Female Comp. | O.D. Comp. | F1960 PEX | F1807 PEX | Female Comp. |
| Connection Type [D]:        | O.D. Comp. | O.D. Comp.   | O.D. Comp.   | O.D. Comp. | F1960 PEX | F1807 PEX | O.D. Comp.   |
| Connection Size             | 1/4"       | 1/4"         | 3/8"         | 3/8"       | 1/2"      | 1/2"      | 5/8"         |

## PRODUCT SELECTOR

| ✓ | Product Number | Description                 | ✓ | Product Number | Description                 |
|---|----------------|-----------------------------|---|----------------|-----------------------------|
|   | 34473          | AA, 1/4" O.D. Compression   |   | 34471          | AA, 1/2" F1960 PEX          |
|   | 34475          | AA, 1/4" Female Compression |   | 34472          | AA, 1/2" F1807 PEX          |
|   | 34465          | AA, 3/8" Female Compression |   | 34467          | AA, 5/8" Female Compression |
|   | 34474          | AA, 3/8" O.D. Compression   |   |                |                             |



\*Limited Lifetime Warranty – See [Oatey.com/warranty](http://Oatey.com/warranty) for details.





**“QUIET PIPES HAVE TONS OF CONNECTION OPTIONS, SO I DON’T WASTE MONEY ON ADDITIONAL JOINTS.”**



**QUIET  
PIPES®**



# OATEY QUIET PIPES® HAMMER ARRESTORS SIZE A-F

## SPECIFICATIONS

Oatey Quiet Pipes Hammer Arrestors shall be installed in any diameter pipe supply application which could experience water hammer due to quick closing valves or faucets. Arrestor chambers shall be specifically sized to accommodate and dissipate energy generated by such valves and faucets. Arrestors shall be effective when installed at any angle. Arrestor shall be made of lead-free copper and include a polypropylene piston with two NBR O-rings. Arrestors shall be ANSI/ASSE1010-2004 certified and approved for installation with no access panel required. Compatible with press fittings or push fittings.

## FEATURES & MATERIALS

|                    |  |
|--------------------|--|
| Arrestor Body      | Copper (Type K)  |
| Piston             | Polypropylene with two NBR O-rings   |
| Piston Lubrication | Dow Corning Molykote 111   |
| Fittings Available | Male Sweat, Female CPVC, MIP, F1807 PEX & F1960 PEX (no lead brass C46400) |

## PERFORMANCE SPECIFICATIONS

|                      |              |
|----------------------|--------------|
| Temperature Range    | 33° – 180° F |
| Max Working Pressure | 0 – 400 PSI  |

## LISTINGS & CODE APPROVALS

|                     |
|---------------------|
| ANSI/ASSE 1010–2004 |
| cUPC                |




## DIMENSIONS


| Arrestor Size               | A         | A      | A         | A          | A           | B          | B      | B           | B         | B         | C           | C      | C          | C         | C         | D          | E      | E          | F      | F          |
|-----------------------------|-----------|--------|-----------|------------|-------------|------------|--------|-------------|-----------|-----------|-------------|--------|------------|-----------|-----------|------------|--------|------------|--------|------------|
| Product #                   | 34476     | 34481  | 34482     | 34486      | 34491       | 34483      | 34484  | 34492       | 34493     | 34495     | 34477       | 34485  | 34487      | 34494     | 34496     | 34488      | 34479  | 34489      | 34480  | 34490      |
| Arrestor Body Diameter [A]: | 1.125"    | 1.125" | 1.125"    | 1.125"     | 1.125"      | 1.125"     | 1.125" | 1.125"      | 1.125"    | 1.125"    | 1.375"      | 1.375" | 1.375"     | 1.375"    | 1.375"    | 1.625"     | 2.125" | 2.125"     | 2.125" | 2.125"     |
| Overall Height [B]:         | 4.78"     | 4.76"  | 4.68"     | 4.87"      | 4.93"       | 5.49"      | 5.39"  | 5.82"       | 5.32"     | 5.6"      | 6.94"       | 6.74"  | 6.87"      | 6.57"     | 6.96"     | 8.29"      | 9.24"  | 9.45"      | 11.23" | 11.41"     |
| Fitting Type [C]:           | F1960 PEX | MIP    | F1807 PEX | Male Sweat | Female CPVC | Male Sweat | MIP    | Female CPVC | F1807 PEX | F1960 PEX | Female CPVC | MIP    | Male Sweat | F1807 PEX | F1960 PEX | Male Sweat | MIP    | Male Sweat | MIP    | Male Sweat |
| Fitting Size [C]:           | 1/2"      | 1/2"   | 1/2"      | 1/2"       | 1/2"        | 1/4"       | 3/4"   | 3/4"        | 3/4"      | 3/4"      | 1"          | 1"     | 1"         | 1"        | 1"        | 1"         | 1"     | 1"         | 1"     | 1"         |

## PRODUCT SELECTOR


| ✓ | Product Number | Description         | ✓ | Product Number | Description         | ✓ | Product Number | Description       | ✓ | Product Number | Description      |
|---|----------------|---------------------|---|----------------|---------------------|---|----------------|-------------------|---|----------------|------------------|
|   | 34476          | A, 1/2" F1960 PEX   |   | 34483          | B, 3/4" Male Sweat  |   | 34477          | C, 1" Female CPVC |   | 34488          | D, 1" Male Sweat |
|   | 34481          | A, 1/2" MIP         |   | 34484          | B, 3/4" MIP         |   | 34485          | C, 1" MIP         |   | 34479          | E, 1" Male Sweat |
|   | 34482          | A, 1/2" F1807 PEX   |   | 34492          | B, 3/4" Female CPVC |   | 34487          | C, 1" Male Sweat  |   | 34489          | D, 1" Male Sweat |
|   | 34486          | A, 1/2" Male Sweat  |   | 34493          | B, 3/4" F1807 PEX   |   | 34494          | C, 1" F1807 PEX   |   | 34480          | F, 1" MIP        |
|   | 34491          | A, 1/2" Female CPVC |   | 34495          | B, 3/4" F1960 PEX   |   | 34496          | C, 1" F1960 PEX   |   | 34490          | F, 1" Male Sweat |




F1960 PEX




F1807 PEX



MIP THREAD



MALE SWEAT




FEMALE CPVC

\*Limited Lifetime Warranty – See [Oatey.com/warranty](http://Oatey.com/warranty) for details.





**“WITH OATEY, I CAN ORDER EVERYTHING  
I NEED WITH A SINGLE PHONE CALL. IT  
COULDN'T BE EASIER.”**



**QUIET  
PIPES®**



deliver quality. build trust. improve lives.

## POWER OF ONE

**#1 in the industry.** Oatey® is the number one source for purchasing the leading brands in the plumbing and home improvement industries.

**One call does it all.** Only Oatey brings you the plumbing industry's best brands in one source. Making it easy to purchase any product across all our brands on one invoice, in one shipment.

**TO PLACE AN ORDER**  
Contact your local Oatey Representative  
800-321-9532  
Oatey.com