

# Quick Hub

## No Hub Couplings

No need to peel off gasket!  
Simply place on pipe



## One and Done

Fastest installation on the market - fits easily and effortlessly onto pipe and fittings. No need to roll gasket, remove shield or waste time fumbling with a loose shield.

With Quick Hub, no need to remove gasket first and roll it over the pipe. The patented hourglass shape design ensures the gasket remains within the shield during shipping and handling and allows the Quick Hub to be easily pushed onto the pipe.

### Three Sealing Rings

Three sealing rings on Quick Hub gaskets outperform others with only two sealing rings.



## Features

40% in labor savings

Gasket and shield do not come apart

### Faster Installation:

Complete jobs quicker to make deadlines

### Neoprene Material

Tested and certified to ASTM C1277, CISPI 310, IAPMO listed

### Fast Assembly:

Assembles over cast iron fitting with ease

### Quick Install

No need to peel back gasket and shield

### Torque Requirements

Same 60-80 lb. torque requirements as regular couplings.

### Field Tested

Tested on high-rise commercial buildings. Tested to perform on min/max pipe diameters

### Three Patents:

US Patent : #10,100,956  
US Patent: #10,253,885  
Us Patent: #10,557,578

Learn more: [www.mifab.com](http://www.mifab.com)